

WEST**End of Result Set**

Generate Collection

Print

L1: Entry 1 of 1

File: DWPI

Jul 18, 1974

DERWENT-ACC-NO: 1974-53973V

DERWENT-WEEK: 197430

COPYRIGHT 2003 DERWENT INFORMATION LTD

TITLE: Tyre press with simple extraction - having lower half of mould free to rotate when press is opened

PATENT-ASSIGNEE:

ASSIGNEE

BRUNOTTE & NIEMEYER GMBH

CODE

BRNT

PRIORITY-DATA: 1973DE-2301414 (January 12, 1973)

PATENT-FAMILY:

PUB-NO

PUB-DATE

LANGUAGE

PAGES

MAIN-IPC

DE 2301414 A

July 18, 1974

000

INT-CL (IPC): B29H 5/02

ABSTRACTED-PUB-NO: DE 2301414A

BASIC-ABSTRACT:

The mould is in two halves sepd. in the plane of the tyre equator. The top half is fixed and has two guides with inclined edges. The lower half, attached to the press ram, can rotate freely and has one guide. The mould charge is loaded into the lower half and, as this is raised to closed the press, its guide slides over the inclined edges of the top guides which causes it to rotate into a central position in which the press completes its closure. Before opening the press, the lower guide is withdrawn, so that the lower half of the mould is free to rotate in line with inclinations or spirals on the tyre.

TITLE-TERMS: TYRE PRESS SIMPLE EXTRACT LOWER HALF MOULD FREE ROTATING PRESS OPEN

DERWENT-CLASS: A35 A95

CPI-CODES: A11-C02A; A12-T01A;

Multipunch Codes: 012 03- 032 359 371 377 380 384 388 41& 45& 483 672

